

1 1/2"

250lpm

# MC 505

## Positive Displacement Flow Meter



METERS

COOL

### > Technical Data

Input – Output: 1<sup>1/2</sup>" x 1<sup>1/2</sup>" Standard (2" Optionally)

Type of flange: ANSI, Square NPT, BSPF

Flow Rate: 25 – 250 lpm (7 – 70 gpm)

Standard measure unit: Litres (US Gallon optionally)

Max Pressure: 10.3 bar (150 Psi)

Repeatability: 0.05%

Accuracy: ±0.12% over a range of 5:1

Viscosity Range: 30 to 1,500,000 SSU (1 to 325,000 cps)

Working Temperature: -30 °C to +70 °C

Absolute compatibility with all Veeder Root components



# Highlights:

- Lack of internal friction (No metal-to-metal contact)
- Reduced number of parts
- Long lifetime
- Self-lubricating
- Low and easy maintenance
- Low drop pressure between parts
- Simple and robust design
- Bi-directional liquid flow
- Meets Worldwide Weights and Measures Standards
- Repeatability under diverse conditions and products



## Advantage

Continuous Accuracy over a wide range of transfer conditions:

- ✓ flow rates
- ✓ pressure rates
- ✓ product temperature variations
- ✓ liquid viscosity

**Meters Control** Positive Displacement Flow meters offer the ideal solution in a variety of applications, in which transfer of petroleum products is implicated and high accuracy is required.

**Meters Control** Positive Displacement flow Meters use the long time proven technology of Tri-Rotor and Vane, with no friction due to the precise accuracy tolerances of the principle.

The **MC** Series Flow Meters are designed and engineered in European Union and they are certified according to:

Directive 94/9/EC (**ATEX**)  
Directive 2004/22/EC (**MID**)

Above European Certificates guarantee Accuracy Repeatability and Long Life.

## TYPICAL APPLICATIONS

Check of loading / unloading operations of fuel and petrochemical products in fuel bulk plants and/or refineries

On truck tanker for fuel transport and delivery

Heavy duty fuel dispensing system for big vehicles and airplanes

NETMILL Co Ltd

SUITE 38-40 LONDON FRUIT EXCHANGE  
BRUSHFIELD ROAD  
LONDON E 1 6 EU - UK  
T: +44 7552956089

NETMIL TRADING Ltd

2 SOFOULI STR.  
8<sup>TH</sup> FLOOR FLAT 803 CHANTECLAIR Bld.  
P.C.:1096 NICOSIA CYPRUS  
T: +357 97773504

WEB: [www.meterscontrol.com](http://www.meterscontrol.com)

SALES: [sales@meterscontrol.com](mailto:sales@meterscontrol.com)

TECHNICAL: [tech@meterscontrol.com](mailto:tech@meterscontrol.com)

